



Tenax Spa

AUTOLUCIDANTE JET

Revision nr.3
Dated 09/05/2011
Printed on 13/06/2011
Page n. 1 / 7

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **AUTOLUCIDANTE JET**
Chemical name and synonym **Resin solution**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Self-polishing paint for stone**

1.3. Details of the supplier of the safety data sheet

Name **Tenax Spa**
Full address **Via I Maggio, 226**
District and Country **37020 Volargne (VR)
Italy**
Tel. **+39 045 6887593**
Fax **+39 045 6862456**

e-mail address of the competent person responsible for the Safety Data Sheet **tenax@tenax.it**

Product distribution by **TENAX ITALY Srl - Via Passo di Napoleone, 778 - 37020 Volargne (Verona) - Italy Tel. +39 045 6860222 - Fax +39 045 6862456 - tenaxitaly@tenaxitaly.it**

1.4. Emergency telephone number

For urgent inquiries refer to **800.883300 (24h) Centro Antiveleni (Bergamo)**

2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.
Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Danger Symbols: Xn

R phrases: 40

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

2.2. Label elements.

Hazard labelling pursuant to Directives 67/548/EEC and 1999/45/EC and subsequent amendments and supplements.



R40 LIMITED EVIDENCE OF A CARCINOGENIC EFFECT.

S36/37 WEAR SUITABLE PROTECTIVE CLOTHING AND GLOVES.

Contains: DICHLOROMETHANE



Tenax Spa

AUTOLUCIDANTE JET

Revision nr.3
Dated 09/05/2011
Printed on 13/06/2011
Page n. 2 / 7

2.3. Other hazards.

Information not available.

3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
DICHLOROMETHANE			
CAS. 75-09-2	50 - 100	Carc. Cat. 3 R40	Carc. 2 H351
EC. 200-838-9			
INDEX. 602-004-00-3			

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

4. First aid measures.

4.1. Description of first aid measures.

EYES: Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.

SKIN: Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists, seek medical attention. Wash contaminated clothing before using them again.

INHALATION: Remove to open air. If breathing is irregular, seek medical advice.

INGESTION: Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Follow doctor's orders.

5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING MEDIA

The extinction equipment should be of the conventional kind: carbon dioxide, foam, powder and nebulised water.

EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products (carbon oxide, toxic pyrolysis products, etc).

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Hardhat with visor, fireproof clothing (fireproof jacket and trousers with straps around arms, legs and waist), work gloves (fireproof, cut proof and dielectric), a depressurised mask with facemask covering the whole of the operator's face or a self-respirator (self-protector) in the event of large quantities of fume.

6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. If there are no contraindications, spray solid products with water to prevent the formation of dust. Use breathing equipment if fumes or powders are released into the air. Block the leakage if there is no hazard. Do not handle damaged containers or the leaked product before donning appropriate protective gear. For information on risks for the environmental and health, respiratory tract protection, ventilation and personal protection equipment, see the



Tenax Spa

AUTOLUCIDANTE JET

Revision nr.3
Dated 09/05/2011
Printed on 13/06/2011
Page n. 3 / 7

other sections of this sheet.

6.2. Environmental precautions.

The product must not penetrate the sewers, surface water, ground water and neighbouring areas.

6.3. Methods and material for containment and cleaning up.

Use inert absorbent material (sand, vermiculite, diatomaceous earth, Kieselguhr, etc.) to soak up leaked product. Collect the majority of the remaining material and deposit it in containers for disposal. If there are no contraindications, use jets of water to eliminate product residues. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage.

7.1. Precautions for safe handling.

Do not smoke while handling and use.

7.2. Conditions for safe storage, including any incompatibilities.

Store in a well ventilated place, keep far away from sources of heat, bright flames and sparks and other sources of ignition.

7.3. Specific end use(s).

Information not available.

8. Exposure controls/personal protection.

8.1. Control parameters.

Name	Type	Country	TWA/8h mg/m ³	ppm	STEL/15min mg/m ³	ppm	
DICHLOROMETHANE	TLV-ACGIH			50			Skin
	OEL	IRL		50		300	Skin
	WEL	UK		100		300	Skin

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration or bad air vent. If such operations do not make it possible to keep the concentration of the product below the permitted workplace exposure thresholds a suitable respiratory tract protection must be used. See product label for hazard details during use. Ask your chemical substance suppliers for advice when choosing personal protection equipment. Personal protection equipment must comply with the rules in force indicated below.

HAND PROTECTION

Protect hands with category III (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVA, butyl, fluoroelastomer or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

EYE PROTECTION

Wear protective airtight goggles (ref. standard EN 166).

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION

If the threshold value for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of breathing protection equipment, such as masks with organic vapour and dust/mist cartridges, is necessary in the absence of technical measures limiting worker exposure. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

An emergency eye washing and shower system must be provided.

The product must be used in a closed cycle, in well-aired environments fitted with strong localised aspiration systems (capture speed > 1.5 m/s), otherwise it is compulsory to use the personal protection equipment indicated and always in well-aired environments fitted with strong localised aspiration systems (capture speed > 1.5 m/s).



Tenax Spa

AUTOLUCIDANTE JET

Revision nr.3
Dated 09/05/2011
Printed on 13/06/2011
Page n. 4 / 7

9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	colourless
Odour	typical
Odour threshold.	Not available.
pH.	Not available.
Melting or freezing point.	Not available.
Boiling point.	Not available.
Distillation range.	Not available.
Flash point.	Not available.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Specific gravity.	1,300 Kg/l
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available.
Ignition temperature.	300 °C.
Decomposition temperature.	Not available.
Viscosity	Not available.
Reactive Properties	Not available.

9.2. Other information.

VOC (Directive 1999/13/EC) :	77,13 % - 1.002,69	g/litre.
VOC (volatile carbon) :	10,90 % - 141,67	g/litre.

10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

DICHLOROMETHANE: decomposes above 120°C. With water and alkalis it may form hydrochloric acid and attack aluminium, copper and alloys.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

DICHLOROMETHANE: risk of explosion on contact with alkaline metals, nitric acid, aluminium (powder), ethanediamine, aluminium chloride, perchloric acid, dinitrogen pentoxide, sodium nitride, n-nitroso n-methylurea, potassium hydroxide. Can react dangerously with: alkaline earth metals, metal powders, sodium amides, potassium tert-butylate. Can form explosive mixtures with the air.

10.4. Conditions to avoid.

None in particular, however the usual precautions used for chemical products should be respected.

DICHLOROMETHANE: avoid exposure to naked flames and hot surfaces.

10.5. Incompatible materials.

DICHLOROMETHANE: aluminium, magnesium powder, sodium, potassium, concentrated nitric acid, caustic agents and strong oxidising agents.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, vapours potentially dangerous to health may be released.

DICHLOROMETHANE: dioxins, phosgenes and hydrochloric acid.

11. Toxicological information.

11.1. Information on toxicological effects.

This product must be handled carefully because of its possible carcinogenic effects. Anyway, currently available data do not allow us to comprehensively assess this product.

DICHLOROMETHANE: Acute toxicity in man: cognitive disorders only if inhaled at very high doses; at 200-500 ppm, nausea, vomiting, dizziness, paresthesia, asthenia and headache have been observed. Skin contact causes pain which soon disappears without any burns. Superficial lesions of the cornea occur on contact with the eyes.



Tenax Spa

AUTOLUCIDANTE JET

Revision nr.3
Dated 09/05/2011
Printed on 13/06/2011
Page n. 5 / 7

DICHLOROMETHANE
LD50 (Oral): 1600 mg/kg Rat
LC50 (Inhalation): 79 mg/l/2h Rat
LD50 (Dermal): > 2000 mg/kg Rat

12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.

DICHLOROMETHANE: not easily biodegradable.

12.3. Bioaccumulative potential.

DICHLOROMETHANE: no appreciable bioaccumulation potential (log Ko/w 1-3).

12.4. Mobility in soil.

DICHLOROMETHANE: very mobile in soil.

12.5. Results of PBT and vPvB assessment.

Information not available.

12.6. Other adverse effects.

Information not available.

13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information.

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations.

These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

Road and rail transport:

ADR/RID Class: 6.1 UN: 1593
Packing Group: III
Label: 6.1
Nr. Kemler: 60
Limited Quantity: 5 lt
Tunnel restriction code: (E)
Proper Shipping Name: DICHLOROMETHANE SOLUTION



Carriage by sea (shipping):

IMO Class: 6.1 UN: 1593
Packing Group: III
Label: 6.1
EMS: F-A, S-A
Marine Pollutant: NO
Proper Shipping Name: DICHLOROMETHANE SOLUTION





Tenax Spa

AUTOLUCIDANTE JET

Revision nr.3
Dated 09/05/2011
Printed on 13/06/2011
Page n. 7 / 7

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review:

The following sections were modified:

01.